

JOTAPROFF Project Wall and Ceiling

Product description

Type

Water soluble, mat, solvent free dispersion paint with low sheen gloss, for indoor use in dry rooms. Project paint which contributes to a labour efficient workday.

Recommended use

Use as a middle and topcoat on walls and in ceilings made by plaster, concrete, sand filler, boards, glass fibre woven fabric etc..

Product data

Packaging size	A-base 10 L (filling level 9 L). Pre-mixed colours: Colour NCS 0502-Y Egg white 10 L and 100 L.
Base availability	A-base
Tinting	Bases must be tinted using Jotun Multicolor . A base: Up to 10 % with Jotun Multicolor colorants.
Colors	Pre-mixed colours: NCS 0502-Y
Gloss level	5
Generic type	PVA dispersion paint, containing acrylic.
Solids by volume	38 ± 2 volume%
Specific gravity	1.5
pH value	8.4 to 8.9
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/a): 30 g/l. The product contains max 1 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well.

Application equipment / methods

Preferred application with roller or airless spray. Apply rich and evenly.

Guiding data for airless spray

Nozzle tip	0.018–0.021"
Spray angle degrees	50–80°
Pressure at nozzle	Min. 15 MPa (Min. 150 kg/cm ²)

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended:	7 - 10	100 - 143	38 - 54

Cleaning of painting tools

Water and **JOTUN Penselrens**.

Thinner

Shall not be thinned.

Conditions during application

Air and surface temperature must be above +10 °C during application.

Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation and film thickness.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	0.5 h
Recoatable, minimum	1 t
Dry to use	24 h
Fully cured	4 weeks

Directions for use

Surface preparation

The substrate must be clean, sound and dry: Clean with **JOTUN Spesialvask før maling**.

Pretreatment

Bare iron and nail heads to be primed with **QUICK Bengalack Grunning**.

Primer

Unpainted absorbent substrates, like wallpaper and unpainted concrete/plastered walls, must be primed before applying middle coat and topcoat. Previously painted: Old glossy/semi glossy paint must be primed with **JOTUN Heftgrunning Universal**. Sand down previously painted, old glossy/semi glossy paint with suitable abrasive paper and remove dust. Ceilings discoloured by soot, nicotine etc.: Prime with **JOTUN Kvist- og sperregrunning**.

Topcoat

2 x **JOTAPROFF Project Wall and Ceiling**. On absorbant, porous surfaces 3 coats are recommended to avoid discolouring.

Cleaning

JOTUN Spezial wipen is recommended to clean spillage. **JOTUN Spezial wipen** is a convenient washing/cleansing wipe for use before and during paint work.

Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time). If cleaning is necessary, the pH of the detergent must not exceed pH 9. **JOTUN Spezialvask før maling** is recommended. For daily cleaning the temperature of the wash water must be <40 °C.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Indoor environment / Emission

The product gives low emission which is measured on a neutral substrate. Substrate and preparation prior to treatment will have an influence on the total emission from finished surface.

Miscellaneous

Contact information

Jotun A/S
Box 2021
NO-3202 Sandefjord
Norway

Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.