

JOTAPROFF PVA 02

Product description

Type

Solvent free waterborne dispersion paint for use indoors in dry rooms.

Recommended use

Use as a middle and topcoat in ceilings made by plaster, concrete, sand filler, boards etc.

Product data

Packaging size	White 3 L, 10 L and 100 L. NCS 0502-Y Egg white 10 L.
Colors	White and NCS 0502-Y Egg white
Gloss level	02
Generic type	PVA copolymer dispersion panit
Solids by volume	32 ± 2 volume%
Specific gravity	1.4
pH value	8.4 to 9.2
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/a): 30 g/l. The product contains max 1 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well.

Application equipment / methods

Preferred application with roller, but brush or airless spray may also be used. Apply rich and evenly.

Guiding data for airless spray

Nozzle tip	0.46-0.53 mm (0.018-0.021")
Spray angle degrees	60-80°
Pressure at nozzle	Min. 15 MPa (Min. 150 kg/cm ²)

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
	7 - 10	100 - 143	32 - 46

Cleaning of painting tools

Water and **JOTUN Penselrens**.

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation and film thickness.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	Ca 1 h
Recoatible, minimum	Ca 3 h
Dry to use	Ca 24 h

Directions for use

Surface preparation

The substrate must be clean, sound and dry: Clean with **JOTUN Spesialvask før maling**. Sand down previously painted, old glossy/semi glossy paint with suitable abrasive paper and remove dust.

Pretreatment

Bare iron and nail heads to be primed with **QUICK Bengalack Grunning**.

Primer

Unpainted absorbent substrates, like wallpaper and unpainted concrete/plastered walls, must be primed before applying middle coat and topcoat. Previously painted: Old glossy/semi glossy paint must be primed with **JOTUN Heftgrunning Universal**. Chalking, bleeding and porous substrates: Should be brushed and then primed with **JOTUN Heftgrunning Universal**. Ceilings discoloured by soot, nicotine etc.: Prime with **JOTUN Kvist- og sperregrunning**.

Topcoat

2 coats JOTAPROFF PVA 02.

Cleaning

JOTUN Spesial wipes is recommended to clean spillage. **JOTUN Spesial wipes** is a convenient washing/cleansing wipe for use before and during paint work.

Maintenance

The product shall not be washed. Washing will cause stains.

Storage

In storage and in transport keep the container frost free and upright.


Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Environmental labelling

The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental labels Svanen (the swan) and the ECO label.



Better for the environment...

- Suitable for indoor use.
- Limited content of hazardous substrates.
- Low solvent content.

... better for you.

NOR/7/1

Better for the environment...

- Suitable for indoor use.
- Limited content of hazardous substrates.
- Low solvent content.

... better for you.

NOR/7/1

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

Contact information

Jotun A/S
Box 2021
NO-3202 Sandefjord
Norway

Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.