

## LADY Balance (2014-2022)

### Product description

#### Type

Acrylic wall paint for smooth walls.

#### Features and benefits

**LADY Balance** gives beautiful matt finish and a good indoor climate. Releases minimal smell and emissions during application and drying.

#### Recommended use

For indoor use on smooth walls in dry rooms. For walls on substrates such as boards / gypsum boards, overpaintable wallpaper, woven fabric, plaster, concrete and putty.

On wooden panel walls, **LADY Supreme Finish** / **LADY Interior Finish** is recommended.



### Product data

**Packaging size** 0,75 L (filling level 0,68 L). 3 L (filling level 2.7 L). 5 L (filling level 4.5 L) and 10 L (filling level 9 L). All packaging sizes may not be available in all markets. Check with your local supplier.

**Base availability** White, A, B and C

**Tinting** If white base is bought as white colour, it shall NOT be tinted using **Jotun Multicolor**. All other colour formulations to be mixed over **Jotun Multicolor**. Up to 10 % with **Jotun Multicolor** colorants.

**Colors** White base may be used untinted as White.

**Gloss level** 05 matt



**Generic type** Acrylic paint.

**Solids by volume** 40 ± 2 volume%

**Specific gravity** 1.4 (white base)

**VOC for Ready-for-Use Mixture** EU limit value for the product (cat. A/a): 30 g/l. The product contains max 1 g/l VOC.

## Application data

### Remarks

Contents of tins with different production numbers should be mixed. Stir well.

### Application equipment / methods

Preferred application with roller, but brush or airless spray may also be used.

### Guiding data for airless spray

<b>Nozzle tip</b>	0.43-0.53 mm (0.017-0.021")
<b>Spray angle degrees</b>	50-80°
<b>Pressure at nozzle</b>	Min. 15 MPa (Min. 150 kg/cm <sup>2</sup> )

The choice of nozzle tip / spray angle / pressure must be adapted to the relevant spray equipment and surface.

### Cleaning of painting tools

Water and **JOTUN Penselrens**.

### Thinner

Shall not be diluted.

### Spreading rate and film thickness

	Spreading rate per coat (m <sup>2</sup> /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
<b>Recommended</b>	8 - 10	100 - 125	40 - 50

### Conditions during application

Temperature of substrate and air must be minimum +10 °C. Air RH max. 70 %.

### Cleaning of spillage

**JOTUN Spezial wipes** are recommended to clean spillage. **JOTUN Spezial wipes** are a convenient washing/ cleansing wipe for use before and during paint work.

### Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation and film thickness.

#### The drying time is measured by stated values:

<b>Relative Humidity (RH)</b>	50 %
<b>Air temperature</b>	23 °C
<b>Substrate temperature</b>	23 °C

<b>Surface (touch) dry</b>	1 h
<b>Recoatable, minimum</b>	2 h
<b>Dry to use</b>	Ca 3 days
<b>Fully cured</b>	4 weeks

## Directions for use

### Surface preparation

The substrates must be clean, dry and free from dust.  
Clean with **JOTUN Spesialvask før maling**. Use gloves.  
Bare iron and nail heads to be primed with **QUICK Bengalack Grunning**.

### Primer

Substrate	Treatment
Chalking, bleeding, absorbing or porous substrates:	Primer: 1 x <b>JOTUN Vegg og tak / LADY Balance</b> .
	Primer : 1 x <b>JOTUN Vegg og tak / LADY Balance</b> .
Textile wall covering:	Primer: 1 x <b>JOTUN Grunning for tapet</b> .
Previously painted surfaces:	Previously painted surfaces must be sanded and cleaned.
Substrates discoloured by soot, nicotine etc.:	Primer: 1-2 X <b>JOTUN Kvist- og sperregrunning</b> .

### Topcoat

2 x **LADY Balance**.  
Apply rich and evenly. The most evenly results is obtained if you roll entire lengths in the same direction on the entire wall.

### Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time). If cleaning is necessary, the pH of the detergent must not exceed pH 9. **JOTUN Spesialvask før maling** is recommended. For daily cleaning the temperature of the wash water must be <40 °C.

### Storage

In storage and in transport keep the container frost free and upright.

### Disposal of waste

Liquid paint and washing water with paint residues must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.

Empty and dry paint buckets in plastic can be sorted together with the plastic packaging, remember to remove the metal handle.  
Check local regulations to learn more about waste management.



## Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

## Certificates

The product is certified by Eurofins Indoor Air Comfort Gold and meets the requirements for emission of VOC.



## Product warranty



More about Jotun's Product Warranty:

**Product Warranty Terms:** Directions for use must be followed.

**The product warranty content:** The product warranty "covers in two coats" means that the surface colour is covered after applying two coats on non-absorbent surfaces. The warranty gives the purchaser the right, to receive new paint, to cover the surface colour. This does not cover the labour cost of the paint work undertaken. Damages to the paint due to defects in the surface or during application are beyond the product warranty. Consumer's rights directed by the law are in addition to, and are not limited by the product warranty.

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

## Miscellaneous

### Contact information

Jotun A/S  
Box 2021  
NO-3202 Sandefjord  
Norway

Tel.: +47 33 45 70 00

### Disclaimer

# Technical Data Sheet

## LADY Balance (2014-2022)



The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).