

## LADY Balance

### Product description

#### Type

Acrylic wall paint for smooth walls.

#### Features and benefits

**LADY Balance** gives beautiful matt finish and a good indoor climate. Releases minimal smell and emissions during application and drying.

#### Recommended use

For indoor use on smooth walls in dry rooms. For walls on substrates such as boards, overpaintable wallpaper, woven fabric, plaster, concrete and putty.

On wooden panel walls, **LADY Supreme Finish / LADY Interior Finish** is recommended.

### Product data

<b>Packaging size</b>	5 L (BASE 4.5 L)
<b>Base availability</b>	White, A, B and C
<b>Tinting</b>	If white base is bought as white colour, it shall NOT be tinted using <b>Jotun Multicolor</b> . All other colour formulations to be mixed over <b>Jotun Multicolor</b> . Up to 10 % with <b>Jotun Multicolor</b> colorants.
<b>Colors</b>	White base may be used untinted as White.
<b>Gloss level</b>	05 matt
<b>Solids by volume</b>	40 ± 2 volume%
<b>Specific gravity</b>	1,4 (white base)
<b>VOC for Ready-for-Use Mixture</b>	EU limit value for the product (cat. A/a): 30 g/l. The product contains max 1 g/l VOC.

### Application data

#### Remarks

Contents of tins with different production numbers should be mixed. Stir well.

#### Application equipment / methods

Preferred application with roller, but brush or airless spray may also be used. Apply rich and evenly.

#### Guiding data for airless spray

<b>Nozzle tip</b>	0.53 mm (0.021")
<b>Spray angle degrees</b>	50–80°
<b>Pressure at nozzle</b>	Min. 15 MPa (Min. 150 kg/cm <sup>2</sup> )

#### Cleaning of painting tools

Water and **JOTUN Penselrens**.

#### Spreading rate and film thickness

	Spreading rate per coat (m <sup>2</sup> /liter)	Recommended film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended	8 - 10	100 - 125	40 - 50

### Conditions during application

Temperature of substrate and air must be minimum +10 °C. Air RH max. 70 %.

### Drying times

Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.

#### The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	10 °C

Surface (touch) dry	1 h
Paintable	2 h
Dry to use	Ca 3 days
Fully cured	4 weeks

## Directions for use

### Surface preparation

The substrate must be clean, sound and dry: Clean with **JOTUN Spesialvask før maling**. Sand down previously painted, old glossy/semi glossy paint with suitable abrasive paper and remove dust.

### Pretreatment

Bare iron and nail heads to be primed with **QUICK Bengalack Metallgrunning**.

### Primer

Textile wall covering to be primed with **JOTUN Grunning for tapet**. Surfaces discoloured by soot, nicotine etc.: Prime with **JOTUN Kvist- og sperregrunning**.

### Topcoat

2 x **LADY Balance**.

### Cleaning of spillage

**JOTUN Spesial wipes** is recommended to clean spillage. **JOTUN Spesial wipes** is a convenient washing/cleansing wipe for use before and during paint work.

### Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time). If cleaning is necessary, the pH value must not be above pH9. **JOTUN Spesialvask før maling** is recommended. For daily cleaning the suds temperature must be <40 °C.

### Storage

In storage and in transport keep the container frost free and upright.

## Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



## Environmental labelling



The product is recognized by Miljømerket Norge, and conforms with the demands of the environmental label Svanen (the swan).

## Certificates

The product is certified by Eurofins Indoor Air Comfort Gold and meets the requirements for emission of VOC.



## Product warranty

More about Jotun's Product Warranty - "**covers in two coats**":

**Product Warranty Terms:** Directions for use must be followed.

**The product warranty content:** The product warranty "covers in two coats" means that the surface colour is covered after applying two coats. The warranty gives the purchaser the right, to receive new paint, to cover the surface colour. This does not cover the labour cost of the paint work undertaken. Damages to the paint due to (hidden) defects in the surface or during application are beyond the product warranty. Consumer's rights directed by the law are in addition to, and are not limited by the product warranty.



## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

## Miscellaneous

### Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.