

## DEMIDEKK Terrassfix (2018)

### Product description

#### Type

Highly efficient detergent, based on biodegradable components. Efficiently removes grease, soot, dirt, surface mold and residues of old wood oil and stain. Brightens the timber before further treatment with **DEMIDEKK Terrasslasyr** or **JOTUN Treolje**.



#### Recommended use

The product cleans, removes previously stained/oiled treatment and brightens impregnated wood. NOTE! Not suitable for use on exotic hardwoods. Not to be used for maintenance cleaning.



### Product data

|                         |                             |
|-------------------------|-----------------------------|
| <b>Packaging size</b>   | 5 L                         |
| <b>Generic type</b>     | Synthetic, basic detergent. |
| <b>Specific gravity</b> | 1 - 1.1                     |
| <b>pH value</b>         | >14<br>ca.                  |

### Application data

#### Remarks

Corrosive liquid. Do not swallow. Keep out of the reach of children. Wear suitable gloves. Use eye protection (e. g. protective goggles). Do not spill on window glass, painted substrates, plastic details or untreated aluminium. It dissolves tarry products like roofing paper, shingle etc. Avoid spraying the product directly onto plants. Any spills may be rinsed off with clean water.

#### Application equipment / methods

Roller or brush.

#### Cleaning of painting tools

Water and **JOTUN Penselrens**.

#### Spreading rate and film thickness

| Spreading rate<br>per coat<br>(m <sup>2</sup> /liter) | Film thickness per coat<br>(µm) |                  |
|---|---------------------------------|------------------|
|   | Wet (calculated)                | Dry (calculated) |

Recommended: 8 - 10 100 - 125

### Thinner

Use unthinned.

## Directions for use

### Surface preparation

Wet the surface with cold water. Pour **DEMIDEKK Terrassfix** into a suitable tray and apply by roller/brush. Leave on for 15–20 minutes. Keep the floor wet by applying more **DEMIDEKK Terrassfix**. Scrub the floor with a stiff brush so that dirt, fungus etc. is completely dissolved. Rinse well with fresh water, use garden hose - not high pressure spray, as this will chip the wood. The product also removes grayed, broken down wood and then some fiber residue can remain. This should be removed by light grinding before treating the wood.

### Finishing treatment

After drying, apply **JOTUN Treolje**, **JOTUN Treolje V** or **DEMIDEKK Terrasslasyr** to the terrace floor.

### Maintenance

Maintain the terrace floor by washing it every year using **JOTUN 2-i-1 Husvask og soppfjerner** / **JOTUN 2-i-1 Husvask och mögeldesinfektion (removes dirt, protects against discolouring fungi and algae and freshens up the colour)**.

### Storage

Frost free storage because the container may burst during freezing. In storage and in transport keep the container upright.

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

### Contact information

Jotun A/S  
Box 2021  
NO-3202 Sandefjord  
Norway

Tel.: +47 33 45 70 00

### Disclaimer

# Technical Data Sheet

## DEMIDEKK Terrassfix (2018)



The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at [www.jotun.com](http://www.jotun.com).