

JOTUN Sopp- og algedreper

Product description

Type

Fungus removing and disinfecting liquid.

Features and benefits

JOTUN Sopp- og algedreper removes fungus. It can also be used as disinfectant of substrates.

The product removes green algae and surface fungi (black spots). Releases minimal smell and emissions during application and drying. Prevents fungus and algae on paint/stain,

Recommended use

The product can be used on untreated, stained, painted or varnished substrates. The product can also be used for disinfection of living quarters, animal quarters, food processing plants etc.

Substrate

All sorts of surfaces.

Product data

Packaging size	Plastic bottle: 1 L
pH value	12 to 13

Application data

Remarks

To be applied after cleaning with **JOTUN 2-i-1 Husvask og soppfjerner** / **JOTUN 2-i-1 Husvask och mögeldesinfektion** / **JOTUN 2-i-1 Husvask/Træ- og Murrens** / **JOTUN 2-i-1 Kraftvask og soppfjerner** / **JOTUN 2-i-1 Kraftvask och mögeldesinfektion** / **JOTUN 2-i-1 Kraftvask/Træ- og Murrens**. Does not attack aluminium, steel, plastics, varnish etc, if used in the recommended mixing ratio. Avoid spraying the product directly onto plants. Any spills may be rinsed off with clean water.

Warning! Irritant. Harmful if swallowed. In case of contact with eyes, rinse immediately with plenty of water.

Application equipment / methods

Washing or white wash brush, sponge, roller, spray bottle or airmix spray equipment

Cleaning of painting tools

Water and / or **JOTUN Penselrens**.

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Comments:	1 liter mixed liquid for approximately 15 m ² .		

Product mixing ratio (by volume)

As fungus remover: 1 part to 10 parts water.
As disinfectant: 1 part to 50 parts water.

Thinner

Water

Conditions during application

JOTUN Sopp- og algedreper react faster when the substrate temperature is above + 20 °C.

Directions for use

Surface preparation

Clean the surfaces with **JOTUN 2-i-1 Husvask og soppfjerner** / **JOTUN 2-i-1 Husvask och mögeldesinfektion** / **JOTUN 2-i-1 Husvask/Træ- og Murrens** or **JOTUN 2-i-1 Kraftvask og soppfjerner** / **JOTUN 2-i-1 Kraftvask och mögeldesinfektion** / **JOTUN 2-i-1 Kraftvask/Træ-og Murrens** (follow the instructions). RINSE THOROUGHLY with fresh water!

Pretreatment

Typical use: Dry, brush and scrape the surface and apply a suitable anti fungal treatment, diluted 1:10 (1 liter to 10 litres of water), using manual spray, brush, sponge etc. Apply sufficient to wet the complete substrate thoroughly and let it dry. Repeat the treatment if necessary.

After cleaning of fungi: Apply JOTUN Sopp- og algedreper to dry surface using hand spray, brush, sponge or similar, diluted 1:10. Apply sufficient to wet the complete substrate thoroughly and let it dry. DO NOT RINSE OFF. Gives best effect above + 20 °C.

After cleaning/disinfection: Dilute JOTUN Sopp- og algedreper 1:50. Disinfectants react faster when the substrate temperature is over +20 °C. Repeat the treatment if necessary, and a higher concentration may in some cases be required.

Used in the correct dilution, it will not affect aluminum, steel, plastic, varnish etc.

Maintenance

Storage

Frost free freight and storage. In storage and in transport keep the container upright.

Disposal of waste

Detergent must not be discharged into drains, but to a reception centre for dangerous waste.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

Contact information

Jotun A/S
Box 2021
NO-3202 Sandefjord
Norway

Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.