

## BUTINOX Terrassebeisfjerner

### Product description

#### Type

**BUTINOX Terrassebeisfjerner** is a powerful alkaline agent for the cleaning of wood.

#### Features and benefits

Effectively removes old oil and stain. **BUTINOX Terrassebeisfjerner** is a powerful detergent for pretreatment of previously stained terrace floor.

For best results, subsequent treatment with **BUTINOX Terrasselysner** is recommended. The treatment lightens the wood and ensures that the colour of the stain is correct. Used for pretreatment of new, weathered and previously stained impregnated materials. Neutralizes terrace stain remover, thus giving a total shorter rinsing time.

#### Recommended use

Used outdoors for all types of wood; terrace floors, furniture, doors and the like. Effectively removes the film of the former oil treatment and brightens wood.

### Product data

<b>Packaging size</b>	5 liter plastic can.
<b>Specific gravity</b>	1.1
<b>pH value</b>	14
	<b>BUTINOX Terrasselysner</b> (pH 1-2) will neutralize <b>BUTINOX Terrassebeisfjerner</b> (pH 14).

### Application data

#### Remarks

**BUTINOX Terrassebeisfjerner** corrodes aluminium and glass! Any spills may be rinsed off with clean water. The product contains potash. Corrosive. Read the hazard label on the packaging.

#### Application equipment / methods

Stain brush, cleaning brush or roller.

#### Spreading rate and film thickness

	Spreading rate per coat (m <sup>2</sup> /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
<b>Recommended:</b>	8 - 10	100 - 125	

#### Thinner

Use unthinned.

## Conditions during application

Temperature of air and substrate must be above +10 °C during painting.

## Directions for use

Substrate	Treatment
Pressure impregnated wood / light woods:	Avoid direct sunlight on the substrate. This reduces the effect. Wet the surface with cold water. Pour <b>BUTINOX Terrassebeisfjerner</b> into a suitable tray and apply by roller/brush. Leave on for 15–20 minutes. Keep the floor wet by applying more <b>BUTINOX Terrassebeisfjerner</b> . Always scrub the floor with a stiff brush so that dirt, fungus etc. is completely dissolved. Rinse well with fresh water, use garden hose - not high pressure spray, as this will chip the wood. If necessary, repeat the cleaning process.
Exotic wood species:	Exotic hardwoods will darken after treatment with <b>BUTINOX Terrassebeisfjerner</b> . To lighten / neutralize, apply <b>BUTINOX Terrasselysner</b> to the wood.  <ol style="list-style-type: none"><li>1. After removing the oil, apply <b>BUTINOX Terrasselysner</b>, while the surface is still wet.</li><li>2. Distribute <b>BUTINOX Terrasselysner</b> with a stain brush or roller.</li><li>3. Wait approx. 5-10 min. and rinse with water.</li></ol>

## Cleaning of spillage

Any spills may be rinsed off with clean water.

## Maintenance

### Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

## Storage

In storage and in transport keep the container frost free and upright.

## Disposal of waste

Empty containers and residues of contents are delivered to municipal waste disposal or nearest environmental station.



## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

## Miscellaneous

### Contact information

Scanox AS  
P.O.Box 904 Brakerøya  
3002 Drammen  
Norway  
Tel: +47 32 24 43 00

### Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.