

pH value

10

Flash point

Closed cup: >62°C (>143.6°F)

Contents

Contains: EDTA < 5 %. Nonionic surfactants < 5 %.

Ingredients

Ammonia solution 24 %  
Dodecylbenzene sulphonic acid  
Tetra sodium ethylenediamine tetraacetate  
Methyl Hydroxyethylcellulose  
Tridecyl Alcohol Ethoxylate



Jotun Protects Property

## JOTUN Spesialrens gulnet panel

### Application data Product description

#### Spreading rate and film thickness

##### Type

| JOTUN Spesialrens gulnet panel is intended for use to application of stain and other transparent products indoors. The product is a concentrate to be diluted with water (1:10). | Spreading rate per coat<br>(m <sup>2</sup> /liter) | Recommended film thickness<br>per coat (µm) |                  |
|--|--|---|------------------|
|  |  | Wet (calculated)                            | Dry (calculated) |

##### Features and benefits

**JOTUN Spesialrens gulnet panel** is a powerful cleanser for yellowed panel. This removes dirt, lignin and fat from yellowed woodwork. The product improves penetration in untreated woodwork. This allows interior stains to penetrate into the woodwork which gives a homogenous, nice appearance. **JOTUN Spesialrens gulnet panel** is a powerful cleaning agent for cleaning very contaminated areas. Wear protective gloves and eye protection.  
1 liter to 10 liters of water.

#### Recommended use Conditions during application

The product is intended for yellowed spruce and pine panel. Can also be used for new woodwork. for best result. It is recommended to wear gloves and goggles. Provide good ventilation.

#### Substrate

Untreated, yellowed spruce and pine. JOTUN Spesialrens gulnet panel can also be used to decrease oily woods like oak and teak. Please note that oak and other hardwoods may become discolored. Perform a test cleaning.

### Directions for use

#### Surface preparation

#### Product data

Clean the woodwork with diluted detergent. Avoid using a stronger solution. Use a clean lint-free cloth or paper. Then wipe the surface with a cloth slightly soaked with clean, lukewarm water. Make sure the woodwork is dry before further processing and that residues of cleaning liquid are removed.

#### Disposal of waste

Detergent must not be discharged into drains, but to a reception centre for dangerous waste.



### Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

---

## **Miscellaneous**

### **Disclaimer**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.