

## LADY Perfection

### Product description

#### Type

Solvent free waterborne dispersion paint for use indoors in dry rooms.

#### Features and benefits

**LADY Perfection** gives a perfect, completely matt ceiling. Easy to apply - without dripping and spilling. Provides a beautiful and stain free result. Wide range of colours. Cover warranty.

#### Recommended use

For smooth ceilings of boards, plaster, concrete, woven fabric and putty. For indoor use in dry rooms. **LADY Supreme Finish / LADY Interior Finish** is recommended for ceilings of wooden panels.

### Product data

<b>Packaging size</b>	White base: 0,75 L (filling level 0,68 L) , 3 L (filling level 2.7 L), 5 L (filling level 4.5 L) and 10 L (filling level 9 L). B-base: 3 L (filling level 2.7 L).
<b>Base availability</b>	White and B.
<b>Tinting</b>	If white base is bought as white colour, it shall NOT be tinted using <b>Jotun Multicolor</b> . Bases must be tinted using <b>Jotun Multicolor</b> . Up to 10 % with <b>Jotun Multicolor</b> colorants.
<b>Colors</b>	White base may be used untinted as White.
<b>Gloss level</b>	Completely matt 02
<b>Solids by volume</b>	33 ± 2 volume%
<b>Specific gravity</b>	1.33
<b>VOC for Ready-for-Use Mixture</b>	EU limit value for the product (cat. A/a): 30 g/l. The product contains max 10 g/l VOC.

### Application data

#### Remarks

Contents of tins with different production numbers should be mixed. Stir well.

#### Application equipment / methods

Preferred application with roller, but brush or airless spray may also be used. Apply rich and evenly.

#### Guiding data for airless spray

<b>Nozzle tip</b>	0.53 mm (0.021")
<b>Spray angle degrees</b>	60-80°
<b>Pressure at nozzle</b>	Min. 15 MPa (Min. 150 kg/cm <sup>2</sup> )

#### Cleaning of painting tools

Water and **JOTUN Penselrens**.

#### Spreading rate and film thickness

	Spreading rate per coat (m <sup>2</sup> /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
<b>Recommended:</b>	8 - 10	100 - 125	33 - 41

### Conditions during application

Surface and air temperature must be minimum +10 °C.

### Drying times

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	1 h
Recoatable, minimum	3 h

## Directions for use

### Surface preparation

The substrate must be clean, sound and dry. Clean with **JOTUN Spesialvask før maling**. Sand down previously painted, old glossy/semi glossy paint with suitable abrasive paper and remove dust.

### Pretreatment

Bare iron and nail heads to be primed with **QUICK Bengalack Grunning**.

### Primer

Chalking, bleeding and porous substrates: Should be brushed and primed with **LADY Vegg 10**.  
Ceilings discoloured by soot, nicotine etc.: Prime with **JOTUN Kvist- og sperregrunning**.

### Topcoat

2 x **LADY Perfection**.

### Cleaning

**JOTUN Spesial wipes** is recommended to clean spillage. **JOTUN Spesial wipes** is a convenient washing/cleansing wipe for use before and during paint work.

### Maintenance

The product shall not be washed. Washing will cause stains.

### Storage

In storage and in transport keep the container frost free and upright.

### Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



## Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

## Product warranty

More about Jotun's Product Warranty:

**Product Warranty Terms:** Directions for use must be followed.

**The product warranty content:** The product warranty "covers in two coats" means that the surface colour is covered after applying two coats on non-absorbent surfaces. The warranty gives the purchaser the right, to receive new paint, to cover the surface colour. This does not cover the labour cost of the paint work undertaken. Damages to the paint due to (hidden) defects in the surface or during application are beyond the product warranty. Consumer's rights directed by the law are in addition to, and are not limited by the product warranty.



## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures,** refer to section 4.

**Handling and storage,** refer to section 7.

**Transport information,** refer to section 14.

**Regulatory information,** refer to section 15.

## Miscellaneous

### Contact information

Jotun A/S  
Box 2021  
NO-3202 Sandefjord  
Norway

Tel.: +47 33 45 70 00

### Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.