

LADY Perfection

Product description

Type

Waterborne dispersion paint for use indoors in dry rooms.




Features and benefits

LADY Perfection gives a perfect, completely matt ceiling. Easy to apply - without dripping and spilling. Provides a beautiful and stain free result. Wide range of colours. Cover warranty.

Recommended use

For smooth ceilings of boards, plaster, concrete, woven fabric and putty. For indoor use in dry rooms. **LADY Supreme Finish / LADY Interior Finish** is recommended for ceilings of wooden panels.



Product data

Packaging size

White base: 0,75 L (filling level 0,68 L). 3 L (filling level 2.7 L). 5 L (filling level 4.5 L) and 10 L (filling level 9 L).
B-base: 3 L (filling level 2.7 L).

Base availability

White base and B-base.

Tinting


If white base is bought as white colour, it shall NOT be tinted using **Jotun Multicolor**.
Bases must be tinted using **Jotun Multicolor**. Up to 10 % with **Jotun Multicolor** colorants.

Colors

White base may be used untinted as White.

Gloss level

Completely Matt 02



Solids by volume

33 ± 2 volume%

Specific gravity

1.33

VOC for Ready-for-Use Mixture

EU limit value for the product (cat. A/a): 30 g/l. The product contains max 10 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well.

Application equipment / methods

Preferred application with roller, but brush or airless spray may also be used. Apply rich and evenly.

Guiding data for airless spray

Nozzle tip	0.43-0.53 mm (0.017-0.021")
Spray angle degrees	50-80°
Pressure at nozzle	Min. 15 MPa (Min. 150 kg/cm ²)

Cleaning of painting tools

Water and **JOTUN Penselrens**.

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended:	8 - 10	100 - 125	33 - 41

Conditions during application

Surface and air temperature must be minimum +10 °C.

Cleaning of spillage

JOTUN Spesial wipen are recommended to clean spillage. **JOTUN Spesial wipen** are a convenient washing/cleansing wipe for use before and during paint work.

Drying times

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	1 h
Recoatable, minimum	3 h

Directions for use

Surface preparation

The substrate must be clean, sound and dry.

Clean with **JOTUN Spesialvask før maling**.

Sand down previously painted old glossy/semi glossy paint with suitable abrasive paper and remove dust.

Bare iron and nail heads to be primed with **QUICK Bengalack Grunning**.

Primer

Substrate	Treatment
Chalking, bleeding and porous substrates:	Should be brushed and primed with LADY Vegg 10 .
Ceilings discoloured by soot, nicotine etc.:	Prime with JOTUN Kvist- og sperregrunning .

Topcoat

2 x **LADY Perfection**.

Maintenance

The product shall not be washed. Washing will cause stains.

Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste



One of our measures to reduce our environmental footprint is to use recycled plastic in the packaging. This bucket consists of up to 60% plastic that you have recycled (PCR). Does not apply to the lid.



Empty and dry pails can be sorted together with plastic packaging. The metal handle must be removed and be sorted with metallic packaging. See the QR code for more information.



Sorted as plastic when empty and dry.



Remove the handle

Liquid paint and washing water with paint residues must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Must be empty and dry

Environmental labelling



2096 0002

The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Green Building Standards

The declared product contributes to Green Building Standard credits by meeting the following specific requirements:

- The emission requirements for M1: Classification of Indoor Environment 2018
- Swan (2096 0002)
- Property criteria in BETA (2018:A2)
- Class B according to Bedömningskriterier (Assessment Criteria) 6.0 for SundaHus (2013)

BREEAM® NOR (2016)

- Hea 02: VOC content for "Interior matt walls and ceilings" (30 g/l) (EU Directive 2004/42/CE) and emission demands (ISO 16000-series).
- Mat 01: Product specific type III EPD (ISO 14025, ISO 21930, EN 15804) for Jotun A/S.
- Mat 01: The product Safety Data Sheet confirms that the product does not contain any substances on the Norwegian A20 list.

Additional certificates and approvals may be available on request.

Product warranty



More about Jotun's Product Warranty:

Product Warranty Terms: Directions for use must be followed.

The product warranty content: The product warranty "covers in two coats" means that the surface colour is covered after applying two coats on non-absorbent surfaces. The warranty gives the purchaser the right, to receive new paint, to cover the surface colour. This does not cover the labour cost of the paint work undertaken. Damages to the paint due to defects in the surface or during application are beyond the product warranty. Consumer's rights directed by the law are in addition to, and are not limited by the product warranty.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Contact information

Jotun Sverige AB
Box 151
421 22 Västra Frölunda
Tlf.: +46 31 69 63 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.