

Fenomastic Güzel Evim Mineral

Product description

Type

This product is a lime matt mineral paint which gives beautiful walls with a limed appearance and unique colour expression.

Features and benefits

This gives a beautiful and matt limestone-like result with a simple application technique.

Recommended use

For smooth walls on substrates such as boards, plaster, concrete and filled substrates indoors, in dry rooms. In areas exposed to wear and when risk of water spilling, transparent protection is recommended.

Product data

Packaging size	1 L and 2.5L
Tinting	The base must be tinted using Jotun Multicolor .
Gloss level	01
pH value	12.4
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/I): 200 g/l. The product contains max 2.54 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well.

Application equipment / methods

Brush: Anza Platinum or Elite. Width optional, but we recommend using 100 mm for application on walls.

Cleaning of painting tools

Water

Film thickness per coat

Typical recommended range

Wet film thickness 100 - 125 µm

The recommended film thickness value applies to the first coat.

Theoretical spreading rate 8 - 10 m²/l

On second coat, a higher consumption must be used, 5-6 m²/l for 2nd coat.

Thinner

The product is ready to use and should not be thinned.

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Drying times

Drying time deviates at changes in temperature, air humidity, air circulation and film thickness.

At 23 °C and 50 % Relative humidity (RH).

Dust dry	1 hour(s)
Dry to over coat, minimum	4 hours.

Directions for use

Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

Recommended paint system

Primer

If the substrate is not uniform, it is recommended to apply two coats of Fenomastic Güzel Evim Zengin Mat, Fenomastic Güzel Evim Saf İpek, Fenomastic Hygiene Silk.

Topcoat

1–2 x Fenomastic Güzel Evim Mineral. Apply with brush - cross brushing/random direction.

Storage

In storage and in transport keep the container frost free and upright.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.