

JOTUN Superheft grunning

Product description

Type

Oil primer with White Spirit. **JOTUN Superheft grunning** is a completely matt, solvent-thinned, tixotropic alkyd primer.

Features and benefits

The product has superior adhesion to most substrates.

Recommended use

For use indoors on glossy, non absorbent substrates where adhesion can be difficult with other primers, such as on tiles in dry rooms, laminate plates and most hard plastics. On plastic and ceramic tiles, it is recommended to perform a test application in order to control adhesion. Can be applied at low temperatures. On new particleboard with waxy surface **JOTUN Heftgrunning universal** is recommended.

Product data

Packaging size	0,75 L (contents 0,68 L) and 3 L (content 2.7 L).
Tinting	Up to 10 % with Jotun Multicolor colorants.
Colors	White. May be tinted to approximate light colours of an A base in Jotun Multicolor Tinting System.
Gloss level	4 completely matt
Generic type	Solvent-thinned thixotropic alkyd primer.
Solids by volume	56 ± 2 volume%
Specific gravity	1.6
Flash point	35 °C Closed cup: 35°C (95°F)
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/g): 350 g/l. The product contains max 350 g/l VOC.

Application data

Remarks

The product is ready for use. Stir well. Contents of tins with different production numbers should be mixed.

Application equipment / methods

Brush or roller.

Cleaning of painting tools

JOTUN Penselrens and water.

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Recommended film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended:	10 - 12	83 - 100	47 - 56

Thinner

The product is ready to use and should not be thinned.

Drying times

Drying times deviates at changes in temperature, humidity, ventilation, film thickness and type of wooden surface. Thick coats, low temperatures may extend the drying time.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	1 h
Paintable	8 h
Dry to use	8 h

Provide adequate heating and ventilation during the curing process.

Directions for use

Surface preparation

The substrate must be clean, sound and dry. Clean with **JOTUN Spesialvask for maling**. Previously painted surfaces must be sanded and cleaned.

Pretreatment

Damages to the substrate and nail holes to be filled with **JOTUN Sparkel for treverk**. Sand and spot prime.

Primer

Apply 1 coat **JOTUN Superheft grunning**.

Topcoat

2 coats **LADY Supreme Finish / LADY Classic 40**.

Cleaning of spillage

JOTUN Spesial wipes is recommended to clean spillage. **JOTUN Spesial wipes** is a convenient washing/cleansing wipe for use before and during paint work.

Maintenance

Must be overpainted within a short time. Hence no need for washing/maintenance.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

Product code: 37182

The first three characters of the Part Number: 26C

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.