

## BUTINOX Interiør Moderne Oljemaling 40

### Product description

#### Type

Waterborne oil paint for woodwork indoors.

#### Features and benefits

Malingen er slitesterk, vaskbar og gir en jevn og glatt overflate.

#### Recommended use

**BUTINOX Interiør Moderne Oljemaling 40** is a paint intended for indoor use. Benyttes som mellom- og oppstrøk på tre, MDF, møbler, dører, karmen og listverk.

### Product data

|                                      |  |
|--------------------------------------|--|
| <b>Packaging size</b>                | 0.75 L (BASE 0.68 L) and 3 L (BASE 2.7 L).   |
| <b>Base availability</b>             | White, A, B and C  |
| <b>Tinting</b>                       | Bases must be tinted.  |
| <b>Gloss level</b>                   | 40 semi gloss  |
| <b>Generic type</b>                  | Waterborne oil paint for indoor use.   |
| <b>Solids by volume</b>              | 34 ± 2 volume%   |
| <b>Specific gravity</b>              | 1.1 - 1.28   |
| <b>pH value</b>                      | 8 to 10  |
| <b>VOC for Ready-for-Use Mixture</b> | EU limit value for the product (cat. A/d): 130 g/l. The product contains max 80 g/l VOC. |

### Application data

#### Remarks

Stir well. Contents of tins with different production numbers should be mixed to avoid possible colour deviations.

#### Application equipment / methods

Brush or roller and brush. Apply rich and evenly.

#### Guiding data for airless spray

|                            |                                  |
|----------------------------|----------------------------------|
| <b>Nozzle tip</b>          | 0.53 mm (0.021")                 |
| <b>Spray angle degrees</b> | 30-50°                           |
| <b>Pressure at nozzle</b>  | 15 MPa (150 kg/cm <sup>2</sup> ) |

Spraying: For professional application only.

### Spreading rate and film thickness

|                     | Spreading rate<br>per coat<br>(m <sup>2</sup> /liter) | Film thickness per coat<br>(µm) |                  |
|---------------------|---|---------------------------------|------------------|
|                     |   | Wet (calculated)                | Dry (calculated) |
| <b>Recommended:</b> | 8 - 10  | 100 - 125                       | 34 - 42          |

### Cleaning of painting tools

Water and brush cleaner.

### Thinner

Shall not be thinned.

### Conditions during application

Temperature of air and substrate must be above +10 °C during painting.

### Drying times

The drying time is affected by temperature, air humidity and film thickness.

#### The drying time is measured by stated values:

|                               |       |
|-------------------------------|-------|
| <b>Relative Humidity (RH)</b> | 50 %  |
| <b>Air temperature</b>        | 23 °C |
| <b>Substrate temperature</b>  | 23 °C |

|                            |     |
|----------------------------|-----|
| <b>Dust dry</b>            | 2 h |
| <b>Recoatable, minimum</b> | 6 h |

## Directions for use

The substrate must be clean and dry.

Surfaces to be washed with **BUTINOX Interiørvask**, matted and dedusted.

Industrial painted panel boards and moldings: Clean first with **TRESTJERNER Gulvrens**, then sand and reclean, before priming with **BUTINOX Interiør Heftgrunn**.

Hard and glossy substrates must be primed with **BUTINOX Interiør Heftgrunn**.

New woodwork, yellowed woodwork or substrates discoloured by soot or nicotine must be primed with a waterborne, stain-blocking and isolating primer.

Damages and roughness of the substrate, as well as board joints and nail heads must be filled with **SCANOX Sparkel for Treverk** and sanded down.

Apply two coats: BUTINOX Interiør Moderne Oljemaling 40.

### Storage

In storage and in transport keep the container frost free and upright.

### Disposal of waste

Empty containers and paint residues must be brought to a community waste disposal or the nearest recycling center.



## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

Product registration number: 4103585

| Safety rules |      |
|--------------|------|
| <b>1-1</b>   | 1993 |

## Miscellaneous

### Contact information

Jotun Danmark A/S  
Jernet 6  
6000 Kolding

Tel: +45 76 30 32 00  
mail@jotun.dk

### Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.