

JOTUN Industri kraftvask

Product description

Type

Strong detergent based on alkalis and other biological raw material degraders. Detergent for cleaning paint lines. **JOTUN Industri kraftvask** can also be used for other tasks that require a powerful detergent with a matting effect.

Features and benefits

JOTUN Industri kraftvask is a powerful detergent which loosens dirt that can't be removed with mild detergents. **JOTUN Industri kraftvask** loosens and removes effectively wet paint, oil, grease, salt, dirt etc. Given adequate working time, **JOTUN Industri kraftvask** may re-solve dry paint (one component paints).

At weaker solution, **JOTUN Industri kraftvask** can be used for easier cleaning tasks.

Recommended use

Powerful detergent for industrial production plants.

Substrate

All sorts of surfaces.

Product data

Packaging size	Plastic packaging: 10 LITER
pH value	13 to 14
Contents	Contains: nonionic surfactants: < 5 %, amphoteric surfactants: < 5 %.
Ingredients	Potassium hydroxide Disodium Ethoxylated alcohols, C16-18 Quartenair C12-C14 alkylaminethoxylate, salt

Application data

Remarks

Will corrode aluminium and glass. May seem mattifying on metal surfaces using high concentration for a long time. Avoid spraying this product directly onto vehicles and bare skin. Any spills may be rinsed off with clean water. May discolor some hard woods.

Warning!

Contains Na-Metasilicate and caustic soda (Kaliumhydroxide). Corrosive liquid. Do not swallow. Keep locked up and out of the reach of children. Avoid contact with skin and eyes. Wear gloves, protective clothing and goggles. In case of spills, rinse immediately with lukewarm water and seek medical attention if necessary. The product contains potash.

Application equipment / methods

Wash brush or high pressure spray with dosing unit. Airless spray must be used with caution. Mechanical treatment will increase the effect of the detergent.

Product mixing ratio (by volume)

1: 2. For simpler cleaning, the product can be diluted up to 1:10.

Directions for use

Remove wet paint and wood fibres by hosing or scraping, before applying the detergent. Dilute with water in ratio 1:2. Apply the detergent and allow to work for 5-10 minutes. Keep the area wet. Scraping/brushing will increase the efficiency. Rinse well.

Application methods, recommended use and technical specifications

See Technical Data Sheet / packaging for the recommended products regarding directions for use, drying times, spreading rate and film thickness etc.

Storage

Frost free storage because the container may burst during freezing. In storage and in transport keep the container upright.

Disposal of waste

Detergent must not be discharged into drains, but to a reception centre for dangerous waste.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.