

JOTUN 2-i-1 Kraftvask og Træ og Murrens

Product description

Type

Detergent for houses to be repainted or restained.

Features and benefits

Powerful special detergent before repainting previously painted/stained surfaces. Prevents discoloration and dirt build-up. Be careful not to get the detergent on self cleaning windows as it may damage the cleaning layer of the glass.

Recommended use

Surfaces to be repainted or restained. The product is also very effective on very contaminated substrates. The product is recommended for outdoor use only.

Substrate

Painted or stained woodwork. Iron, masonry, concrete and tiles. Not to be used on boats, cars or caravans.

Product data

Packaging size 1 liter and 4 liter.

Generic type Synthetic, alkalic detergent

Specific gravity 1.07 pH value 7 to 9

(diluted with water 1:10)

Contents Contains: 1-10% cationic surfactants and 1-10% non-ionic surfactants.

Ingredients Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

didecyldimethylammonium chloride

Alcohols, C9-11, ethoxylated

Citric acid Glycerin propane-2-ol

Quaternary C12-14 alkyl methyl amine ethoxylate methyl chloride

sodium hydroxide

Application data

Remarks

Use gloves to avoid drying of the skin. Avoid contact with eyes. Avoid working in direct sunlight (will loose effect). Avoid spraying this product directly onto plants, vehicles and bare skin. May discolor some hard woods.

Application equipment / methods

Washing- or scrubbing brush, high pressure spray with dosing unit. Mechanical treatment will increase the effect of the detergent.

High pressure cleaner must be used with caution. The distance between nozzle and surface: Min. 30 cm. Pressures over 70 bar: The distance to the wall/substrate and the spray angle must be increased further. Intense stream or the use of "turbo nozzle" could destroy cladding surface in total, and should therefore be avoided.

Cleaning of painting tools

Date of issue: 02.03.2021 Product code: 38043 Product family: Not Page: 1/3

Technical Data Sheet JOTUN 2-i-1 Kraftvask og Træ og Murrens



Rinse with water.

Spreading rate and film thickness

	Spreading rate per coat (m²/liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Comments:	1 liter mixed liquid for		

approximately 15 m².

Product mixing ratio (by volume)

1 liter to 10 liters of water.

Directions for use

Surface preparation

Dilute with water in ratio 1:10 (1 liter to 10 litres of water) by normal cleaning. Apply to dry surface. On vertical surfaces the detergent should be applied from below and upwards. Should be left 3-5 minutes to work and keep the area wet. Rinse well from above and downwards.

Cleaning

Any spills may be rinsed off with clean water.

Storage

Frost free storage because the container may burst during freezing. In storage and in transport keep the container upright.

Disposal of waste

Detergent must not be discharged into drains, but to a reception centre for dangerous waste.





Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4. Handling and storage, refer to section 7. Transport information, refer to section 14.

Regulatory information, refer to section 15.

Date of issue: 02.03.2021 Product code: 38043 Product family: Not Page: 2/3

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

Technical Data Sheet JOTUN 2-i-1 Kraftvask og Træ og Murrens



Miscellaneous

Contact information

Jotun A/S Box 2021 NO-3202 Sandefjord Norway

Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

Date of issue: 02.03.2021 Product code: 38043 Product family: Not Page: 3/3 available.

This Technical Data Sheet supersedes those previously issued.