

LADY Wonderwall

Product description

Type

Very durable, matt, water-soluble acrylic paint.

Features and benefits

The coating has excellent washability, a stain-resistant and highly durable surface and provides no stains after washing. Guaranteed to cover in two coats.

Recommended use

For walls on substrates such as boards / gypsum boards, overpaintable wallpaper, woven fabric, plaster, concrete and putty. Particularly suitable for surfaces with high requirements for washability and rooms exposed to heavy use. On wooden panel walls, **LADY Supreme Finish** / **LADY Interior Finish** is recommended.

Product data

Packaging size	0,75 L (filling level 0,68 L), 3 L (filling level 2.7 L), 5 L (filling level 4.5 L) and 10 L (filling level 9 L).
Base availability	White, A, B and C
Tinting	Bases must be tinted using Jotun Multicolor . If white base is bought as white colour, it shall NOT be tinted using Jotun Multicolor . Up to 10 % with Jotun Multicolor colorants.
Colors	White base may be used untinted as White.
Gloss level	05 matt
Solids by volume	42 ± 2 volume%
Specific gravity	1.41 (white base)
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/a): 30 g/l. The product contains max 1 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed. Stir well.

Application equipment / methods

Roller, brush or airless spray.

Guiding data for airless spray

Nozzle tip	0.53 mm (0.021")
Spray angle degrees	65–80°
Pressure at nozzle	Min. 15 MPa (Min. 150 kg/cm ²)

Cleaning of painting tools

Water and **JOTUN Penselrens**.

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended:	8 - 10	100 - 125	42 - 52

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation and film thickness.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Surface (touch) dry	1 h
Recoatable, minimum	2 h
Cured	4 weeks

Directions for use

Surface preparation

The substrates must be clean, dry and free from dust.
Clean with **JOTUN Spesialvask før maling**. Use gloves.

Substrate	Treatment
Bare metal (bare iron and nail heads):	Primer: 1 x QUICK Bengalack Grunning / QUICK Bengalack Metallgrunning . Topcoat : 2 x LADY Wonderwall .
Chalking, bleeding, absorbing or porous substrates:	Primer: 1 x JOTUN Vegg og tak / LADY Wonderwall . Topcoat: 2 x LADY Wonderwall .
Unpainted wallboards / gypsum boards, overpaintable wallpaper / woven fabric:	Primer: 1 x JOTUN Vegg og tak / LADY Wonderwall . Topcoat: 2 x LADY Wonderwall .
Textile wall covering:	Primer: 1 x JOTUN Grunning for tapet . Topcoat: 2 x LADY Wonderwall .
Previously painted surfaces:	Previously painted surfaces must be sanded and cleaned. Topcoat: 2 x LADY Wonderwall .
Substrates discoloured by soot, nicotine etc.:	Primer: 1-2 x JOTUN Kvist- og sperregrunning . Topcoat: 2 x LADY Wonderwall .

Cleaning

JOTUN Spezial wipes is a convenient washing/cleansing wipe for use before and during paint work.

Maintenance

Newly painted surfaces must not be cleaned the first four weeks (the product's curing time). If cleaning is necessary, the pH of the detergent must not exceed pH 9. **JOTUN Spezialvask før maling** is recommended. For daily cleaning the temperature of the wash water must be <40 °C.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Remove as much paint residue from brush / tool as possible with water and brush cleaner. Empty containers and residues of contents are delivered to municipal waste disposal or nearest environmental station.



Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Product warranty

Guaranteed to cover in two coats. More about Jotun's Product Warranty:

Product Warranty Terms: Directions for use must be followed.

The product warranty content: The product warranty "covers in two coats" means that the surface colour is covered after applying two coats on non-absorbent surfaces. The warranty gives the purchaser the right, to receive new paint, to cover the surface colour. This does not cover the labour cost of the paint work undertaken. Damages to the paint due to (hidden) defects in the surface or during application are beyond the product warranty. Consumer's rights directed by the law are in addition to, and are not limited by the product warranty.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.