

## LADY Minerals Revive

### Product description

#### Type

A natural matte wall renewer to be used indoors in dry rooms, on walls with moderate load.



#### Features and benefits

**LADY Minerals Revive** is a wall renewer that makes it easier to transform uneven surfaces into a mineral look. The product provides a vibrant surface with unique color expressions. Efficient to apply and easy to distribute. Can be applied in 0-4 mm thickness without cracking. Minimal shrinkage. Very good adhesion to the surface. Note that it can be challenging touching up **LADY Minerals Revive**, because you may experience getting visible patches.

#### Recommended use

Painted fiberglass wall coverings and painted textile wallpaper for indoor use in dry rooms. Can be used to plastered masonry and other rough wall surfaces. Can be used on plain, painted walls when a mineral, concrete-like appearance is desired. Absorbent, non-painted wallpaper / substrates should be primed. For extra protection of outer corners - in exposed areas - a corner protector can be fitted.



### Product data

<b>Packaging size</b>	10 L (filling level 9 L)
<b>Base availability</b>	Revive
<b>Tinting</b>	The base must be tinted using <b>Jotun Multicolor</b> .
<b>Colors</b>	Is available in selected <b>LADY</b> colors.
<b>Gloss level</b>	Completely matt 01
<b>Solids by volume</b>	52 ± 2 volume%
<b>Specific gravity</b>	1.15
<b>Particle size</b>	0 - 0.25 mm
<b>pH value</b>	8.3 to 9.9

## Application data

### Remarks

Stir well before and during use. When using several cans, the last 2 liters should be mixed and stirred into the next can.

### Application equipment / methods

Roll and spatula.

Apply with Jordan Ultimate paint roller for even surface 18cm, extender shaft attached. Use Jordan trowel 25 cm to even out the wall renewer. It is recommended to grind / round the pointed edges on the trowel.

Mask with suitable masking tape. Use blue or yellow quality tape.

Avoid breaks and overlapping stains on the wall on the last coat. The product on the wall can be moistened very carefully with a shower spray, if the transition is dry. Then use the trowel to even out well.

Carefully remove the masking tape when the wall renewer is dry.

After the work is finished: Carefully remove dust with a dry, lint free microfibre cloth. Do not use a vacuum cleaner on the wall.

### Consumption (application)

On a very rough surface, up to 2 liters / m<sup>2</sup> can be expected in a two-stroke system.

The first coat should be applied very rich, and fully cover the surface texture and color.

The second coat should be applied thinner.

### Conditions during application

Air and surface temperature must be above +10 °C during application. Recommended temperature is 18–23 °C.

### Cleaning of painting tools

Water

Clean painting tools and trowel with water or **JOTUN Spesial wipes**. Ensure that the dried product / grain does not get mixed into the container. Gently wipe the edges of the can with water using a spray, to prevent the can edges from drying. When applying the last coat, the trowel must be kept free of dried product and small grain. Paint roller to be wrapped well in a tight plastic bag for storage until the next day and application of the next coat.

Spills on lists or the floor can be easily removed with a damp cloth / **JOTUN Spesial wipes**.

### Drying times

The second coat usually dries faster than the first coat.

#### The drying time is measured by stated values:

<b>Relative Humidity (RH)</b>	50 %
<b>Air temperature</b>	23 °C
<b>Substrate temperature</b>	23 °C

<b>Surface (touch) dry</b>	15 h
<b>Recoatable, minimum</b>	24 h

## Directions for use

Surface preparation:	Cover with quality masking tape against lists etc. Protruding unevenness of the wall is removed with a spatula / wallpaper knife. Any "bubbles" or unevennesses in the wallpaper are cut away with a sharp wallpaper knife. Moisten the dry roller slightly with water. Dip the paint roller until it is fully covered with the product, if necessary, use a sponge for application in smaller areas.
First coat:	Start on one side of the wall and apply the product from the middle and roll towards the ceiling / list and apply the product rich. If the product glues and moisturizes poorly on the wall, leave for 5 minutes and re-roll with more of the product. First coat should cover / erase structure and substrate color as much as possible. Use a wide filler spade to smooth the product. Distribute the mass evenly over the wall - not too wide field at a time. Avoid making holes or craters in the smoothed surface. Smaller runs and edges by the trowel are acceptable. The product dries on the surface after about 15 minutes. If the product is too dry in overlap zones, the surface may be sprayed very carefully with a little water. Finish the wall. The first coat will have dried completely after 1 day.
Second coat:	Use a broad trowel to cut off stripes / unevenness. Then, dust off the wall with dry, lint free microfibre cloth. Apply the second coat using the same procedure as the first coat, but use a smaller amount of the product. Avoid unilateral diagonal smoothing if using a spatula, instead use oval movements. Begin to smooth the surface from the wall's outer edges and work your way towards the center. If you experience blistering, these will disappear by further smoothing of the surface. Smooth the surface completely to avoid craters. Small, thin stripes / degrees in the surface after smoothing are acceptable. On very rough surfaces you may need to apply 3 layers.
Final finish - after drying:	Remove masking tape. Use wide spatula to cut off irregularities. Make sure you do not cut deep grooves with the edges of the spatula. Carefully remove dust with a dry, lint free microfibre cloth. Do not wash the wall with water.

## Additional information

Please refer to [jotun.no/ladyminerals](https://www.jotun.no/ladyminerals) for a film and advice regarding application methods.  
<https://www.jotun.com/dk/da/b2c/products/interior/lady/lady-minerals-revive-how-to.aspx>  
<https://www.jotun.com/no/no/b2c/products/interior/lady/lady-minerals-revive-how-to.aspx>  
<https://www.jotun.com/se/se/b2c/products/interior/lady/lady-minerals-revive-how-to.aspx>

## Cleaning

Spills on lists or the floor can be easily removed with a damp cloth / **JOTUN Spesial wiper**.

## Storage

In storage and in transport keep the container frost free and upright.

## Disposal of waste

The product must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



## Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

## Miscellaneous

### Contact information

Jotun A/S  
Box 2021  
NO-3202 Sandefjord  
Norway

Tel.: +47 33 45 70 00

### Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.