

TREBITT Terrassebeisfjerner (2019)

Product description

Type

Strong cleaning agent based on alkalis and other biological raw material degraders.

Recommended use

The product cleans, removes previously stained/oiled treatment and brightens impregnated wood.

Remark: Wear gloves and goggles. Do not spill on window glass, painted substrates, plastic details or untreated aluminium. Unngå søl på andre steder enn flatene som skal renses. Corrosive hazard!















Product data

Packaging size 4 L

Generic type Synthetic, alkalic detergent

Specific gravity 1.08 pH value 14

Application data

Remarks

Corrosive liquid. Keep out of the reach of children. Do not swallow. Irritant. Wear suitable gloves. Use eye protection (e.g. protective goggles).

Do not spill on window glass, painted substrates, plastic details or untreated aluminium. Corrosive hazard! It dissolves tarry products like roofing paper, shingle etc. Avoid spraying the product directly onto plants. Any spills may be rinsed off with clean water.

Application equipment / methods

Brush or roller.

Cleaning of painting tools

Water and JOTUN Penselrens.

Consumption

8-10 m²/liter.

Thinner

Use unthinned.

Date of issue: 12.03.2019 Product ID: 41562 Product 22T Page: 1/3 code:

This technical data sheet supersedes those previously issued.

Technical Data Sheet

TREBITT Terrassebeisfjerner (2019)



Directions for use

Avoid direct sunlight on the substrate. This reduces the effect.

1)	Moisten the substrate lightly with cold water. Avoid ponds with water.
2)	Pour TREBITT Terrrassebeisfjerner (2019) into a suitable tray and apply by brush/roller in a limited work area. Should be left 15-20 minutes to work.
3)	Keep the floor wet by applying more TREBITT Terrrassebeisfjerner (2019) with brush mounted on an extender shaft. Massage TREBITT Terrassebeisfjerner (2019) into the substrate with a brush repeatedly. Keep the area moist using TREBITT Terrassebeisfjerner (2019) during the active time. Let the product, in combination with light scrubbing with a brush, do the cleaning job.
4)	Scrub the floor lightly with a terrace scrub with extension shaft. Scrub the tree's longitudinal direction to counteract wood fiber defuzzing.
5)	Rinse well with plenty of water. Use garden hose - not high pressure washer since this will splinter the surface of the timber. The terrace floor can be treated after drying with TREBITT Terrassebeis . Please note! Incorrect working method or weathered decking can give defuzzing frayed wood surface. If required, it is recommended to lightly sand before treatment with TREBITT Terrassebeis or JOTUN Treolje .

Remarks



Click here to see our "how-to film":

 $\underline{https://www.jotun.com/no/b2c/how-to/video/how-to-stain-previously-stained-terrace.aspx}$

Maintenance

Storage

Frost free storage because the container may burst during freezing. In storage and in transport keep the container upright.

Disposal of waste

Liquid cleaning agent must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.





Date of issue: 12.03.2019 Product ID: 41562 Product 22T Page: 2/3 code:

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

Technical Data Sheet TREBITT Terrassebeisfjerner (2019)



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

Date of issue: 12.03.2019 Product ID: 41562 Product 22T Page: 3/3 code:

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.