

## Marine Rubbing Pro

---

### Product description

#### Type

This is a state of the art rubbing liquid.

#### Features and benefits

Specially designed for removal of scratches, oxidized surfaces, dirt and stains.

#### Recommended use

To be used for rubbing and polishing of gelcoat and two component paints. Can also be used on light metals.

### Packaging (typical)

	Volume (litres)	Size of containers (litres)
Marine Rubbing Pro	1	1

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

### Product data

<b>Colours</b>	light beige		
<b>pH value</b>	7		
<b>Flash point</b>	>100 °C		
<b>VOC</b>	65	g/l	US EPA method 24

### Application data

#### The product can be applied by

Cotton, Rag, Sponge, 3M pad: Recommended.

#### Product mixing ratio (by volume)

Single pack

#### Cleaning of painting tools

Water

---

## Directions for use

### Surface preparation

Surfaces with grease, oil or other contamination, wash with recommended Jotun Yachting detergent.

### Pretreatment

Shake the can before use. Apply the product with a clean, soft and moist cloth. Machine application is recommended at a rotating speed of approximately 1000 - 1500 rpm. Polish to the desired effect. For manual polishing, rub by hand with circular movements, only smaller areas at the time. Polish to the desired effect. Complete with a clean microfibre cloth or polish paper.

### Finish coat

Finish with a Jotun Yachting wax.

### Remarks

Do not apply the product on hot surfaces or in direct sunlight. Avoid contact with plastic details.

### Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

### Shelf life at 23 °C

Marine Rubbing Pro 24 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

---

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

---

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

# Technical Data Sheet

## Marine Rubbing Pro



---

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.