

Textile PowerClean

Product description

Type

This is a chloride containing, water-based care product, for stain removal on outdoor textiles.



Features and benefits

Effectively removes heavy stains and dirt.

Recommended use

To be used for cleaning canopies, pillows, life jackets, rugs, awnings and other outdoor textiles.

Product data

Packaging (typical)

**Volume
(litres)**

**Size of containers
(litres)**

Textile PowerClean

1

1

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

Colours

yellowish shade

Density

1 g/cm³ calculated

Contents

Contains: chlorine-based bleaching agents <5 %.

VOC

0 g/l US EPA method 24

The provided data is typical for factory produced products, subject to slight variation depending on colour.

Application data

Application methods

Mix with advantage in a spray bottle and spray on the surface. Can also be applied with a sponge or lint-free cloth. When using a spray bottle, the bottle must be emptied after use.

Product mixing ratio (by volume)

Single pack

Thinner/Cleaning solvent

Thinner: Water

Cleaning of painting tools

Water

Directions for use

Surface preparation

The fabric should be rinsed and loose dirt removed.

Pretreatment

Shake well before use. For contaminated surfaces dilute the product with water at a ratio of 1:5. Clean the surface using a soft brush or a sponge. For heavily contaminated surfaces, use undiluted product. Allow to work 10-15 minutes. The product should only be used on colour resistant textiles. Rinse well with fresh water.

Topcoat

Textile Watershield. Refer to TDS, direction for use for the selected Jotun Yachting product.

Additional information

The product should only be used on colour resistant textiles. It is recommended to test the product in a small visible place first if you are unsure.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Textile PowerClean 18 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Caution

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Jotun representative for approval before commencing the work.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Product registration number: 4216395

Safety rules

00-4

1993

Colour variation

When applicable, products primarily meant for use as primers or antifoulings may have slight colour variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

Colour and gloss retention on topcoats/finish coats may vary depending on type of colour, exposure environment such as temperature, UV intensity etc., and application quality. Contact your local Jotun office for further information.

Miscellaneous

Contact information

Jotun A/S
Box 2021
NO-3202 Sandefjord
Norway

Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.