Technical Data Sheet



Textile PowerClean

Product description

Туре

This is a chloride containing waterbased product.

Features and benefits

Effectively removes heavy stains and dirt.

Recommended use

To be used for cleaning of sprayhoods, rugs, awnings and other outdoor textiles.

Packaging (typical)

	Volume (litres)	Size of containers (litres)
Textile PowerClean	1	1

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

Product data

Colours	yellowish shade		
pH value	12.9		
Contents	Contains: chlorine-based bleaching agents <5 %.		
VOC	0	g/l	US EPA method 24

Application data

The product can be applied by

Cotton, Rag, Sponge, 3M pad: Recommended.

Product mixing ratio (by volume)

Single pack

Thinner

Water

Cleaning of painting tools

Water

Date of issue: 24.01.2020

Product code: 44982

Page: 1/3

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

Technical Data Sheet Textile PowerClean



Directions for use

Surface preparation

Textile Cleaner. Refer to TDS, direction for use for the selected Jotun Yachting product.

Pretreatment

Shake well before use. For contaminated surfaces dilute the product with water at a ratio of 1:5. Clean the surface using a cloth or spray pump. For heavily contaminated surfaces, use undiluted product. Allow to work 10-15 minutes. Lightly scrub the surface with a moisten sponge, brush or cloth. Rinse well with fresh water.

Recommended paint system

Finish coat

Textile Watershield. Refer to TDS, direction for use for the selected Jotun Yachting product.

Remarks

The product should be used on colour resistant textiles.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Textile PowerClean

36 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet. **First-aid measures**, refer to section 4. **Handling and storage**, refer to section 7. **Transport information**, refer to section 14. **Regulatory information**, refer to section 15.

Date of issue: 24.01

24.01.2020

Product code: 44982

Page: 2/3

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.



Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue: 24.01.2020

Product code:

44982

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.