

## JOTUN Letspartel Grov 6789

---

### Product description

#### Type

Pre-mixed, coarse-grained light filler with excellent filling properties.

#### Features and benefits

The product is very easy to apply and sand. The filler has a particularly high degree of filling capacity and minimal shrinkage. The product provides a uniform surface. If a finer final texture is required, JOTUN Letspartel Medium 5678 can be used as the final filler.

#### Recommended use

For use indoors in dry rooms for the filling of walls and ceilings on substrates such as concrete, light concrete, plaster and plasterboard.

---

### Product data

<b>Packaging size</b>	According to the current price list.		
<b>Colours</b>	Light grey		
<b>Generic type</b>	EVA polymer dispersion based, creamed hand filler with white spheric aluminium silicate, expanded perlite and dolomite.		
<b>Specific gravity</b>	1		
<b>Particle size</b>	0.3	mm	max
<b>pH value</b>	7 to 8		

---

### Application data

#### Application equipment / methods

To be applied with a spatula.

#### Cleaning of painting tools

Filler on the skin can be removed using soap and water. The tool should be cleaned with water before the filler dries. Dried filler can be removed by soaking in water.

#### Spreading rate and film thickness

**Comments:** 1 m<sup>2</sup>/litre for 1 mm thick layer.

## Drying times

Depending on film thickness, substrate type, temperature, humidity, ventilation.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature 23 °C

Substrate temperature 23 °C

Recoatible, minimum 8-10 hours

## Directions for use

### Surface preparation

All substrates shall be firm, clean and free from dust and loose particles.

### Filler

To be applied with a trowel in a thickness of 0-8 mm. When applying in thicknesses of over 4 mm, the filler should be applied in several layers and be almost completely dry between each application. This reduces the total drying time. Too early application of the next layer increases the risk of shrinkage and the formation of cracks.

### Topcoat

Use Jotun's recommended interior products.

### Storage

In storage and in transport keep the container frost free and upright. Min. 12 months if unopened packaging, cool storage.

## Environmental labelling



The product is recognized by Miljømærkning Danmark, and conforms with the demands of the environmental label Svanen (the swan).

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

Product registration number: Not to be declared

Safety rules

00-1

1993

---

## Contact information

Jotun Danmark A/S  
Jernet 6  
6000 Kolding  
Tlf.: +45 76 30 32 00  
Mailadresse: mail@jotun.dk

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.