

JOTUN Letspartel Medium 5678

Product description

Type

Pre-mixed light filler with low density and high filling ratio.

Features and benefits

The product is CE labeled and certified according to EN13963.

Recommended use

The filler is used indoors in dry rooms for the extensive levelling of walls and ceilings constructed from plaster, concrete, light concrete, plasterboard, etc. Can also be used to fill plasterboard joints together with paper strips. The product can also be used for filling plasterboard where joint tape is used.

Product data

Packaging size	According to the current price list.		
Colors	Light grey		
Generic type	EVA polymer dispersion based, creamed hand filler with expanded perlite and dolomite - does not contain flyash.		
Specific gravity	1.1		
Particle size	0.2	mm	max
pH value	8 to 9		

Application data

Application equipment / methods

To be applied with a spatula.

Cleaning of painting tools

Filler on the skin can be removed using soap and water. The tool should be cleaned with water before the filler dries. Dried filler can be removed by soaking in water.

Thinner

Shall not be diluted.

Spreading rate and film thickness

Comments: When covering the whole area: 1 m²/litre for 1 mm thick layer. For filling plasterboard joints: 0.3 liter/m².

Film thickness per coat (µm)
Wet (calculated) Dry (calculated)

Conditions during application

Application temperature +10 °C to +25 °C. 40-80 % RF.

Drying times

Depending on film thickness, substrate type, temperature, humidity, ventilation.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Air temperature 23 °C

Substrate temperature 23 °C

Recoatable, minimum 8 - 10 hours

Directions for use

Surface preparation

All substrates shall be firm, clean and free from dust and loose particles.

Primer

Any priming prior to filling should be undertaken using JOTUN Microgrunder DK/JOTUN Mikrogrunder Extra DK.

Filler

Can be applied in thicknesses of up to 4 mm. Thicker layers significantly extend the drying time. It can be advantageous to apply the filler in several layers, allowing it to dry between each application. Cured filler: The filler is not water-resistant.

Topcoat

Use Jotun's recommended interior products.

Storage

In storage and in transport keep the container frost free and upright. Shelf life: Min. 12 months if unopened packaging, cool storage.


Environmental labelling



The product is recognized by Miljømærkning Danmark, and conforms with the demands of the environmental label Svanen (the swan).

Approvals

CE-marking



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Contact information

Jotun Sverige AB
Box 151
421 22 Västra Frölunda
Tlf.: +46 31 69 63 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.