

JOTUN Tapetlim 1234

Product description

Type

Water-thinned adhesive for the hanging of wallpaper in dry, heated rooms.

Features and benefits

The adhesive is reinforced with added EVA polymer dispersion.

Product data

Colors	White
Generic type	Modified adhesive reinforced with an EVA copolymer dispersion. Creamy, thixotropic consistency.
Solids by volume	14 ± 2 volume%
Specific gravity	1.03

Application data

Remarks

Stir well before use.

Application equipment / methods

The adhesive is well-suited to machine application.

Cleaning of painting tools

Lukewarm water.

Thinner

May, if necessary be thinned with a small amount of water.

Spreading rate and film thickness

Comments: Coverage: 4 m² per litre.

Conditions during application

The temperature of the air and substrate shall be 18-25°C.

Drying times

Ensure good ventilation during the work.

Directions for use

Surface preparation

The substrate shall be clean, firm, dry, non-chalky and free from residual wallpaper, etc. Sealed and painted substrates should be sanded and washed with JOTUN Spesialvask før Maling.

Primer

In the event of a need for adhesion to / priming of bare plaster, thinned adhesive can be applied. Chalky or highly-absorbent substrates should be primed using **JOTUN Microgrunder DK** or **JOTUN Microgrunder Extra DK** after cleaning.

Adhesive

The adhesive should be stirred before use and uniformly applied to the back of the wallpaper so that it is absorbed and softens the wallpaper before hanging. Avoid getting adhesive on the front side of the wallpaper. Any residual adhesive on the front of the wallpaper should be removed, either by lightly wiping the paper with a damp sponge or by washing with a sponge, depending on the quality of the wallpaper. Immediately remove any residual adhesive with a damp cloth.

The wallpaper can be painted when the adhesive is completely dry.

Storage

In storage and in transport keep the container frost free and upright. Shelf life approx. 1 year in unopened packaging when stored in a cool, dry place.

Environmental labelling



The product is recognized by Miljømærkning Danmark, and conforms with the demands of the environmental label Svanen (the swan).

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Contact information

Jotun Sverige AB
Box 151
421 22 Västra Frölunda
Tlf.: +46 31 69 63 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.