

## **BoatWash**

## **Product description**

#### **Type**

This is an alkaline waterborne detergent.

#### **Features and benefits**

The product removes grease, salt and dirt. It is biological degradable. For normal cleaning the product can also be diluted with sea water, but it is important to rinse with fresh water afterwards.

#### **Recommended use**

To be used as a detergent for gelcoat and wooden boats both outside and inside. Painted or varnished surfaces can be cleaned, but dilute the product with water at a ratio of 1:50 - 1:100 to avoid risk of mattening. Can be used for cleaning the engine and engine rooms.

## Packaging (typical)

Volume (litres) Size of containers (litres)

BoatWash 1

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

## **Product data**

**Colours** colourless

pH value 11

**Contents** Contains:

nonionic surfactants: 15-30 % amphoteric surfactants: < 5 %

**VOC** 0 g/I US EPA method 24

# **Application data**

#### The product can be applied by

Brush: Recommended.

Cotton, Rag, Sponge, 3M pad: May be used.

Date of issue: 29.01.2019 Product code: 9180 Page: 1/3

# Technical Data Sheet BoatWash



## **Product mixing ratio (by volume)**

Single pack

#### **Thinner**

Water

## **Directions for use**

#### **Surface preparation**

For contaminated surfaces dilute the product with water at a ratio of 1:50 - 1:100. For heavily contaminated surfaces dilute the product with water at a ratio of 1:20. Clean the surface using a soft brush or a sponge. Can also be applied with a low pressure washer, cleaned with a sponge. Rinse well with fresh water. Not recommended for daily maintenance cleaning.

For cleaning the engine apply the product undiluted onto the surface with a clean cloth and leave to work 10-15 minutes. Rinse well with fresh water.

#### **Remarks**

Use gloves.

### **Storage**

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

### Shelf life at 23 °C

BoatWash 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

# **Health and safety**

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Date of issue: 29.01.2019 Product code: 9180 Page: 2/3

# Technical Data Sheet BoatWash



## **Disclaimer**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.