

Textile Watershield

Product description

This is a solvent based impregnation.

Features and benefits

It gives very good water proof and dirt repellent surface. It is fast drying. It protects the surface against ageing and wear.

Typical use

To be used on sprayhoods, rugs, awnings and similar items of cotton and nylon materials.

Product data

	Volume (liters)	Size of containers (liters)
Textile Watershield	1	1

The volume stated is for factory made colors. Note that local variants in pack size and filled volumes can vary due to local regulations.

Colors clear to light yellow

Density 0.78 g/cm³ calculated

The provided data is typical for factory produced products, subject to slight variation depending on color.

Application data

Recommended: Spray

May be used: Cotton, Rag, Sponge, 3M Pad

Cleaning of painting tools

Jotun Thinner No. 2

Film thickness per coat (μm)	
Wet (calculated)	Dry (calculated)

Product mixing ratio (by volume)

Single pack

Directions for use

Surface preparation

Textile Cleaner. Refer to TDS, direction for use for the selected Jotun Yachting product.

Pretreatment

Areas with mould and green algae, use recommended Jotun Yachting products. For best result, the substrate should be clean, dry and free from any contamination.

Topcoat

Shake the can before use. Spray a uniform layer on the surface and let it dry.

Additional information

Do not apply the product on hot surfaces or in direct sunlight. Do not spray the product on plastic window.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Textile Watershield 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Note

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Jotun representative for approval before commencing the work.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Color variation

When applicable, products primarily meant for use as primers or antifoulings may have slight color variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

Color and gloss retention on topcoats/finish coats may vary depending on type of color, exposure environment such as temperature, UV intensity etc., and application quality. Contact your local Jotun office for further information.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

48662017

NOBB module number

41557786

Contact information

Jotun A/S
Box 2021
NO-3202 Sandefjord
Norway

Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.