Technical Data Sheet



Textile Watershield

Product description

Туре

This is a solvent based impregnation.

Features and benefits

It gives very good water proof and dirt repellent surface. It is fast drying. It protects the surface against ageing and wear.

Recommended use

To be used on sprayhoods, rugs, awnings and similar items of cotton and nylon materials.

Product data

Colours			
Flash point	65 °C		
VOC-USA	750	g/l	EPA Method 24
Contents	Contains: cationic surfa	ctants: < 5 %	

Packaging (typical)

	Volume (litres)	Size of containers (litres)		
Textile Watershield	1	1		
The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.				

Application data

The product can be applied by

Brush: Recommended. Cotton, Rag, Sponge, 3M pad: May be used.

Product mixing ratio (by volume)

Single pack

Cleaning of painting tools

Jotun Thinner No. 2

Date of issue: 23.09.2014.

by Jotun Group

Page: 1/2

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.



Directions for use

Surface preparation

Textile Cleaner. Refer to TDS, direction for use for the selected Jotun Yachting product.

Pretreatment

Areas with mould and green algae, use recommended Jotun Yachting products. For best result, the substrate should be clean, dry and free from any contamination.

Finish coat

Shake the can before use. Spray a uniform layer on the surface and let it dry.

Remarks

Do not apply the product on hot surfaces or in direct sunlight. Do not spray the product on plastic window.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Textile Watershield

48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health- and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet. First-aid measures, refer to section 4. Handling and storage, refer to section 7. Transport information, refer to section 14. Regulatory information, refer to section 15.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue: 23.09.2014.

Page: 2/2

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.