Technical Data Sheet



Hard Wax

Product description

Туре

This is a nano technology based wax.

Features and benefits

The wax particles ensure a deep mirror shine and long lasting protection. It is easy to apply. The product tolerates degreasing. Specially designed for non weathered and thoroughly polished surfaces.

Recommended use

To be used on gelcoat and two component paints.

Product data

	Volume	Size of containers	
	(liters)	(liters)	
Hard Wax	0.5	0.5	
The volume stated is for factory made colors.	Note that local variants in pacl	size and filled volumes can vary	

The volume stated is for factory made colors. Note that local variants in pack size and filled volumes can vary due to local regulations.

Colors	yellowish shade	
Density	0.75 to 0.8 g/ cm ³	calculated

The provided data is typical for factory produced products, subject to slight variation depending on color.

Application data

The product can be applied by

Cotton, Rag, Sponge, 3M Pad: Recommended.

Cleaning of painting tools

Water

Product mixing ratio (by volume)

Single pack

Directions for use

Date of issue:

21.10.2021

Product code: 9190

Product family:

9PY

Page: 1/3

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.



Surface preparation

Surfaces with grease, oil or other contamination, wash with recommended Jotun Yachting detergent.

Pretreatment

Treat the surface with a Jotun Yachting cleaner, rubbing or polish. Refer to TDS, direction for use for the selected Jotun Yachting product.

Topcoat

Shake the can before use. Apply a thin layer of the product with a clean and soft cloth. Allow to dry for 10-15 minutes. Complete with a clean microfibre cloth or polish paper. For machine polishing, recommended rotating speed is approximately 1000 rpm.

Additional information

Do not apply the product on hot surfaces or in direct sunlight.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Hard Wax

48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Note

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Jotun representative for approval before commencing the work.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

Product code:

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Color variation

Date of issue: 21.10.2021

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

Product family:

9PY

Page: 2/3

9190

Technical Data Sheet

Hard Wax



When applicable, products primarily meant for use as primers or antifoulings may have slight color variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

Color and gloss retention on topcoats/finish coats may vary depending on type of color, exposure environment such as temperature, UV intensity etc., and application quality. Contact your local Jotun office for further information.

Miscellaneous

Contact information

Jotun A/S Box 2021 NO-3202 Sandefjord Norway

Tel.: +47 33 45 70 00

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

Date of issue: 21.10.2021

This technical data sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.

Product family:

9PY

Page: 3/3

9190

Product code: