# **Technical Data Sheet**



## Shiny

## **Product description**

#### Туре

This is a wax polish. It is based on special combination of very fine polishing agent and synthetic wax.

#### **Features and benefits**

It cleans, polishes and protects the surface in one operation.

#### **Recommended use**

To be used for cleaning, polishing and protection of gelcoat and two component paints.

### **Product data**

Colours	light green		
Flash point	65 °C		
VOC-USA	210	g/l	EPA Method 24
VOC-Solvent Emission Directive	1,76	g/kg	SED (1999/13/EC)

## Packaging (typical)

	Volume (litres)	Size of containers (litres)
Shiny	0.5	0.5
The volume stated is for factory made colours.	Note that local variants in pac	k size and filled volumes can varv

### **Application data**

due to local regulations.

#### The product can be applied by

Cotton, Rag, Sponge, 3M pad: Recommended.

#### Product mixing ratio (by volume)

Single pack

#### **Cleaning of painting tools**

Water

Date of issue: 23.09.2014.

by Jotun Group

Page: 1/2

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.



### **Directions for use**

#### Surface preparation

Surfaces with grease, oil or other contamination, wash with recommended Jotun Yachting detergent.

#### Pretreatment

Shake the can before use. Apply the product with a clean, soft and moist cloth. Polish to the desired effect. Complete with a clean microfibre cloth or polish paper.

#### Remarks

Do not apply the product on hot surfaces or in direct sunlight. The surface can be washed after 24 hours. Avoid contact with rubber and plastic details.

#### Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

#### Shelf life at 23 °C

Shiny

48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

### Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health- and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14. Regulatory information, refer to section 15.

### Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue: 23.09.2014.

by Jotun Group

Page: 2/2

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.