Technical Data Sheet



Chrome Polish

Product description

Туре

This is a nano technology based polish.

Features and benefits

It leaves a high gloss surface with excellent water and stain protection.

Recommended use

To be used for polishing chrome and stainless steel surfaces. Not to be used on light metals.

Product data

Colours	beige		
Flash point	95 °C		
VOC-USA	0	g/l	EPA Method 24

Packaging (typical)

	Volume (litres)	Size of containers (litres)
Chrome Polish	0.5	0.5
The volume stated is for factory made colours	Note that local variants in pack	size and filled volumes can vary

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

Application data

The product can be applied by

Soft cloth, Polish paper: Recommended.

Product mixing ratio (by volume)

Single pack

Cleaning of painting tools

Water

Date of issue: 23.09.2014.

by Jotun Group

Page: 1/2

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.



Directions for use

Surface preparation

Surfaces with grease, oil or other contamination, wash with recommended Jotun Yachting detergent.

Pretreatment

Shake the can before use. Apply the product on the area to be treated. Polish to the desired effect. Complete with a clean microfibre cloth or polish paper. For machine polishing, recommended rotating speed is approximately 1000 rpm.

Remarks

Do not apply the product on hot surfaces or in direct sunlight. Avoid contact with rubber and plastic details.

Storage

Do not store below 0°C or above 35°C. The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Chrome Polish

36 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health- and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet. First-aid measures, refer to section 4. Handling and storage, refer to section 7. Transport information, refer to section 14. Regulatory information, refer to section 15.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue: 23.09.2014.

by Jotun Group

Page: 2/2

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.